## FAST 6000 PUMP PRO PLUS WIDE




Fog emission and saturation: up to  $6000 \text{ m}^3$  in 80 seconds (2000 m³ visibility less than 1 m)

A powerful and fast fogging system, ideal to protect large areas like big shops, warehouses, superstores or even to protect targets in open space.

It is arranged to an easy wall installation (bracket included)

and it has a side compartment to equip boards or accessories if needed.







Weight of the fogging machine	around 49 Kg
Weight with packaging	around 52 Kg
Units on one pallet (100×120 cm)	4
Dimension of the machine	L 44,0 x W 30,5 x H 43,5 cm
Dimension of the packaging	L 61,0 x W 49,0 x H 62,5 cm
Color	white
Working time without mains power	around 3 hours
Heating time from cold	around 2,5 hours
Vertical mounting	yes (bracket included)
Horizontal mounting	no
Usb port for computer monitoring	yes
Nozzle tamper	yes
Serial interface RS232 with UR FOG Standard protocol	yes
Lan Connection : Active Cloud	opzional
Heating system "Layer"	yes
Coverage in a single shot (visibility more than 1,5 m)	up to 6000 m³
Coverage in a single shot (visibility less than 1 m)	up to 2000 m³
Max seconds of fog emission	80 sec
Max fog emitted with full fog bag	6800 m³
Number of bag	1
Fog tank capacity	1x 4000 ml
Shooting specification	programmable in seconds
Bag included	1
ELECTRICAL SPECIFICATIONS	
Mains power	230 V or 120 V
Average power consumption	80 W
7,2 Ah 12V back up battery (not included)	yes
Pir sensor validation input	yes
Shot confirmation output	yes








## The protection capacity of over 10 fogging systems in just 1 fogging system

## FAST 6000 PUMP PRO PLUS WIDE



**2** FOGGING SYSTEMS : 1,2 KW at start 200 WATT during operation



**10** FOGGING SYSTEMS: From 10 to 15 KW at start 1 KW during operation

Solution with other products

